

# WHT6SYB

**gorenje**  
Life Simplified

## Freestanding wall decorative cooker hood



**B**



AdaptLight



Easy-to-clean filters



OptiStart



Recirculation mode



Touch control

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **Painted steel/glass / varnished steel**

Lightning efficiency class: **A**

Grease filtering efficiency class: **B**

Fluid dynamic efficiency class: **B**

Maximum extraction rate by extraction operation: **650 m<sup>3</sup>/h**

Maximum extraction rate by recirculation operation: **488 m<sup>3</sup>/h**

Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **235 m<sup>3</sup>/h**

Air flow by extraction version, step 2: **345 m<sup>3</sup>/h**

Air flow by extraction version, step 3: **650 m<sup>3</sup>/h**

Electronic control

Control setting: **Touch control**

Number of speed positions: **3**

OptiStart - just one push of the on/off button to start the hood

TouchFree Inox

Lamp type: **LED**

AdaptLight

Number of lights: **2**

Power of lights: **6 W**

Filter material: **Washable aluminium with polyurethane foam**

Coal filter code (optional as separate purchase): **698059**

Number of filters: **2**

Recirculation set number: **683038**

Number of motors: **1**

No return airflow flap: **150 mm**

Max. noise level: **70 dB(A)re 1 pW**

Height: **42 mm**

Min. height of the chimney: **740 mm**

Max. height of the chimney: **980 mm**

Annual energy consumption: **69.7 kWh**

Dimensions (W×H×D): **59.8 × 4.2 × 45.6 cm**

Dimensions of packed product (W×H×D): **70.8 × 59 × 49.1 cm**

Net weight: **14.3 kg**

Gross weight: **18.9 kg**

Connected load: **266 W**

Nominal current of fuse: **16 amp**

Product code: **732385**

EAN code: **3838782164491**



<https://international.gorenje.com/product/732385>